

GDO-6 EasyRoller®

600N SLIM DRIVE ROLL UP GARAGE DOOR OPENER

The slim fit GDO-6 EasyRoller® is an international standard in door automation. Designed in Australia and exported to the world, it's reputation is built on the following features:

Safety







Drive & Mounting Systems





Operating Modes & Features







auto close







Optional Extras





smart | simple | secure



from gate to garage

Technical Specifications		GDO-9 Enduro™	GDO-9 Dynamo™	GDO-11 Ero™	GDO-6 EasyRoller®	GDO-8 Shed Master®
Input/Motor Voltage		230Vac - 240Vac 50Hz / 24Vdc				
Transformer Rating		150VA	100VA	72VA	100VA	72VA
Standby power		2.2W	2.2W	2.2W	2.2W	2.8W
C-Rail Options	1-piece Aluminium C-Rail with Belt	Standard	N/A	N/A	N/A	
	1-piece Aluminium C-Rail with Chain	Optional	N/A	N/A		
	1- or 4-piece Steel C-Rail with Chain	N/A	Standard	Standard		
	1- or 4-piece Steel C-Rail with Belt	N/A	Optional	Optional		
Min. Headroom (top of C-Rail to highest point of door travel)		72mm	57mm	57mm	N/A	N/A
Min./Rec. Sideroom (curtain edge to inside of door bracket)		N/A	N/A	N/A	40mm/80mm	40mm/80mm
Weather-Resistant Rating		IP20	IP20	IP20	IP20	IP24
Maximum Door Area		18.0m ²	16.5m²	13.5m²	16.5m²	13.5m ²
Peak Lifting Force		1,000N	800N	650N	600N	550N
Typical Travel Speed		110mm/sec	130mm/sec	140mm/sec	120mm/sec	100mm/sec
Receiver storage capacity		14 x 4 button Transmitters	14 x 4 button Transmitters	8 x 4 button Transmitters	14 x 4 button Transmitters	8 x 4 button Transmitters
Receiver/Transmitter type		Multi-frequency UHF FM (434.37, 433.47 & 433.92MHz)				
Coding type		Code hopping (Non-linear encryption algorithm)				
No. of code combinations		4.29+ billion random codes				
Warranty		2 year / 5,000 cycle parts warranty				
Optional /	Accessories & Outputs					
Battery Backup		✓	✓	✓	✓	×
SmartSolar™		✓	✓	✓.	✓	√
Auxiliary Output		√	✓	✓	✓	V